

## [2017 Newest 300-175 Exam Dumps Free Download In Lead2pass 100% 300-175 Exam Questions (141-160)]

Lead2pass 2017 September New Cisco 300-175 Exam Dumps! [100% Free Download!](#) [100% Pass Guaranteed!](#) Test your preparation for Cisco 300-175 with these actual 300-175 new questions below. Exam questions are a sure method to validate one's preparation for actual certification exam. Following questions and answers are all new published by Cisco Official Exam Center:

<https://www.lead2pass.com/300-175.html> QUESTION 141ScenarioIn this scenario, you will refer to screenshots about Cisco UCS B-Series servers and UCS Manager.InstructionsTo access the multiple-choice questions, click on the numbered boxes on the left of the top panel.There are four multiple-choice questions with this task.Be sure to answer all four questions before selecting the Next button. Refer to the screenshot in Exhibit 3. Which tab would you choose to determine that a user failed to login to Cisco IMC? A. Fault SummaryB. System Event LogC. CIMC LogD. Logging ControlsAnswer: CExplanation:

[http://www.cisco.com/en/US/docs/unified\\_computing/ucs/c/sw/gui/config/guide/1.5/b\\_Cisco\\_UCS\\_C-series\\_GUI\\_Configuration\\_Guide.151\\_chapter\\_01110.html#d85279e21a1635](http://www.cisco.com/en/US/docs/unified_computing/ucs/c/sw/gui/config/guide/1.5/b_Cisco_UCS_C-series_GUI_Configuration_Guide.151_chapter_01110.html#d85279e21a1635) QUESTION 142ScenarioIn this scenario, you will refer to screenshots about Cisco UCS B-Series servers and UCS Manager.InstructionsTo access the multiple-choice questions, click on the numbered boxes on the left of the top panel.There are four multiple-choice questions with this task.Be sure to answer all four questions before selecting the Next button. Refer to the screenshot in Exhibit 4. Once you enable an SNMP Trap destination, which SNMP Version is required to configure the Inform Trap Type? A. 1B. 2C. 2cD. 3 Answer: DExplanation:

[http://www.cisco.com/c/en/us/td/docs/switches/datacenter/sw/5\\_x/nx-os/system\\_management/configuration/guide/sm\\_nx\\_os\\_cg/sm\\_9snmp.html](http://www.cisco.com/c/en/us/td/docs/switches/datacenter/sw/5_x/nx-os/system_management/configuration/guide/sm_nx_os_cg/sm_9snmp.html) QUESTION 143ScenarioIn this scenario, you will refer to screenshots about Cisco UCS B-Series servers and UCS Manager.InstructionsTo access the multiple-choice questions, click on the numbered boxes on the left of the top panel.There are four multiple-choice questions with this task.Be sure to answer all four questions before selecting the Next button. Refer to the screenshot in Exhibit 5. Which of the following user roles allows the permission Clear All Logs? A. read-onlyB. userC. operatorD. system Answer: CExplanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0\\_chapter\\_01001.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-0/b_UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_01001.html) QUESTION 144Which three parameters can be configured for a vHBA? (Choose three.) A. Enable persistent binding.B. Enable a hardware-based failover.C. Define a SAN pin groupD. Assign a QoS policy.E. Define an MTU.F. Assign a MAC address. Answer: ACDEExplanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-1/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_1/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_1\\_chapter\\_011010.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-1/b_UCSM_GUI_Configuration_Guide_2_1/b_UCSM_GUI_Configuration_Guide_2_1_chapter_011010.html) QUESTION 145With Cisco UCS Manager, in which location do you monitor the chassis discovery process? A. CMCB. FSMC. CDPD. DME Answer: BExplanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0\\_chapter\\_0100011.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-0/b_UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_0100011.html) QUESTION 146Which two protocols does the Cisco Integrated Management Controller support for managing standalone Cisco UCS -Series servers? (Choose two.) A. SoLB. IPMIC. IPMIv2 D. SMASH CLPE. SNMPv3 Answer: CEEExplanation:

<http://www.cisco.com/c/dam/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/at-a-glance-c45-737177.pdf> QUESTION 147Which three statements about what occurs when a Cisco UCS -Series Blade Server connects to the SAN across a fabric interconnect that is enabled in Fibre Channel NPV mode are true? (Choose three.) A. The server ports in F Port mode are pinned to the NP Ports.B. The E Ports are pinned to the E Ports on the fabric interconnect.C. Zoning is deployed on the fabric interconnect.D. The fabric interconnect is not assigned a Fibre Channel domain ID.E. Traffic that is received on the server ports in F Port mode from the server side is pinned to the NPIV-enabled uplink ports on the fabric interconnect.F. The fabric interconnect must have the Fibre Channel uplink port connected to the upstream switch F Port in NPIV mode that performs the Fibre Channel forwarder function. Answer: ADE QUESTION 148You plan to implement FCoE on a Cisco UCS -Series server. Which option must you configure from the Cisco Integrated Management Controller GUI? A. a vNIC failoverB. a boot table entryC. NIVD. FIP mode Answer: DExplanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/c/sw/gui/config/guide/1-2-1/b\\_Cisco\\_UCS\\_CSeries\\_Servers\\_Integrated\\_Management\\_Controller\\_Configuration\\_Guide\\_1\\_2\\_1/Cisco\\_UCS\\_CSeries\\_Servers\\_Integrated\\_Management\\_Controller\\_Configuration\\_Guide\\_1\\_2\\_1\\_chapter9.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/gui/config/guide/1-2-1/b_Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1/Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1_chapter9.html) QUESTION 149Refer to the exhibit. Which tables correctly map the HIF ports to active FEX NIF ports on a Cisco UCS 2208X IOM in discrete pinning mode? A. Table 2 and Table 4B. Table 1 and Table 4C. Table 2 and Table 3D. Table 1 and Table 2E. Table 3 and Table 4 Answer: BExplanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting\\_chapter\\_01001.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting_chapter_01001.html)

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/c/sw/gui/config/guide/1-2-1/b\\_Cisco\\_UCS\\_CSeries\\_Servers\\_Integrated\\_Management\\_Controller\\_Configuration\\_Guide\\_1\\_2\\_1/Cisco\\_UCS\\_CSeries\\_Servers\\_Integrated\\_Management\\_Controller\\_Configuration\\_Guide\\_1\\_2\\_1\\_chapter9.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/gui/config/guide/1-2-1/b_Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1/Cisco_UCS_CSeries_Servers_Integrated_Management_Controller_Configuration_Guide_1_2_1_chapter9.html) QUESTION 149Refer to the exhibit. Which tables correctly map the HIF ports to active FEX NIF ports on a Cisco UCS 2208X IOM in discrete pinning mode? A. Table 2 and Table 4B. Table 1 and Table 4C. Table 2 and Table 3D. Table 1 and Table 2E. Table 3 and Table 4 Answer: BExplanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting\\_chapter\\_01001.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting_chapter_01001.html)

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting\\_chapter\\_01001.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting_chapter_01001.html)

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting\\_chapter\\_01001.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ts/guide/UCSTroubleshooting/UCSTroubleshooting_chapter_01001.html)

[ml](#) QUESTION 150 You have a Cisco UCS C-Series Server. What can you use to log the blade server statistics? A. the Cisco Integrated Management Controller log B. RADIUS C. LDAP D. the XML API Answer: A Explanation:

<http://www.cisco.com/c/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/datasheet-c78-733571.html>

QUESTION 151 You manage Cisco UCS -Series Rack-Mount Servers. Which three components can you upgrade by using the Cisco Host Upgrade Utility? (Choose three.) A. the LAN on motherboard B. the Cisco Integrated Management Controller C. the operating system images D. the system BIOS E. the fabric interconnects F. the FEX modules Answer: ABDE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/c/sw/lomug/2-0-x/b\\_huu\\_2\\_0\\_3/b\\_huu\\_2\\_0\\_3\\_chapter\\_01.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/sw/lomug/2-0-x/b_huu_2_0_3/b_huu_2_0_3_chapter_01.html)

QUESTION 152 Which three components are parts of the Cisco UCS -Series Blade Server software bundle? (Choose three.) A. the adapter firmware B. the Kernel and system firmware for fabric interconnects C. the BIOS firmware D. the IOM firmware E. the Cisco UCS Manager software F. the board controller firmware Answer: ACE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/firmware-mgmt/gui/2-2/b\\_GUI\\_Firmware\\_Management\\_22/b\\_GUI\\_Firmware\\_Management\\_22\\_chapter\\_0100.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/firmware-mgmt/gui/2-2/b_GUI_Firmware_Management_22/b_GUI_Firmware_Management_22_chapter_0100.html)

QUESTION 153 Which slot(s) contain DIMMs in a 1DPC configuration on Cisco UCS blade server? A. 0 B. 1 and 2 only C. 1 D. 2 Answer: CE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/hw/blade-servers/install/B200.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/hw/blade-servers/install/B200.html)

QUESTION 154 Which destination(s) are valid for syslog messages for a Cisco UCS Fabric Interconnect? A. a file and monitor only B. the log, the monitor and syslog queue C. the console D. the console and log only E. a file F. the console, the monitor, and a file Answer: F Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/ucsm\\_syslog/b\\_Monitoring\\_Cisco\\_UCSM\\_Using\\_Syslog/b\\_Monitoring\\_Cisco\\_UCSM\\_Using\\_Syslog\\_chapter\\_010.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/ucsm_syslog/b_Monitoring_Cisco_UCSM_Using_Syslog/b_Monitoring_Cisco_UCSM_Using_Syslog_chapter_010.html)

QUESTION 155 Which two statements about the provisioning of Cisco VM-FEX DirectPath I/O mode are true? (Choose two.) A. The VT-D feature on the ESX host server must be disabled before you can enable VM DirectPath. B. VM-FEX standard mode is the same as VM-FEX high-performance mode. C. Enabling high performance turns on VM DirectPath mode. D. VM DirectPath mode prevents the use of VMware vMotion. E. To use Cisco VM-FEX DirectPath I/O mode, a virtual machine must have a dynamic vNIC and two static vNICs on the VIC adapter. Answer: CE Explanation:

[http://www.cisco.com/c/en/us/solutions/collateral/data-center-virtualization/unified-computing/vm\\_fex\\_best\\_practices\\_deployment\\_guide.html](http://www.cisco.com/c/en/us/solutions/collateral/data-center-virtualization/unified-computing/vm_fex_best_practices_deployment_guide.html)

QUESTION 156 Which maintenance action releases the assigned chassis ID for future use? A. acknowledge chassis B. reset CMOS C. decommission chassis D. remove chassis Answer: CE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-2/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_2/managing\\_the\\_chassis.html#task\\_EB93895D63664D86ACDE9D13C222A452](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-2/b_UCSM_GUI_Configuration_Guide_2_2/managing_the_chassis.html#task_EB93895D63664D86ACDE9D13C222A452)

QUESTION 157 Which authentication provider requires a custom attribute? A. TACACS+ B. RADIUS C. LDAP D. local authentication Answer: A Explanation:

[http://www.cisco.com/en/US/docs/unified\\_computing/ucs/sw/gui/config/guide/141/UCSM\\_GUI\\_Configuration\\_Guide\\_141\\_chapter\\_7.html](http://www.cisco.com/en/US/docs/unified_computing/ucs/sw/gui/config/guide/141/UCSM_GUI_Configuration_Guide_141_chapter_7.html)

QUESTION 158 Which two descriptions of the Call Home feature on a Cisco UCS server are true? (Choose two.) A. uses Java to generate predefined reports B. provides an email-based notification for critical system policies C. provides all the information to administrators, who can open a case with one click D. delivers alerts to multiple recipients, including Cisco TAC, and generates a case by using Cisco TACE. E. provides a central repository for storing fault data Answer: BDE Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/1-3-1/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_1\\_3\\_1/UCSM\\_GUI\\_Configuration\\_Guide\\_1\\_3\\_1\\_chapter39.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/1-3-1/b_UCSM_GUI_Configuration_Guide_1_3_1/UCSM_GUI_Configuration_Guide_1_3_1_chapter39.html)

QUESTION 159 Which two policies can specify that a port channel be configured between the fabric extender and fabric interconnect? (Choose two.) A. chassis or fabric extender discovery policy B. rack server discovery policy C. rack management connection policy D. server inheritance policies E. autoconfig policies F. chassis connectivity policy Answer: AF Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0\\_chapter\\_01100.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-0/b_UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_01100.html)

QUESTION 160 From the Cisco UCS Manager GUI, which two configurations can be performed for Cisco UCS C-Series Rack-Mount Servers from the rack server discovery policy? (Choose two.) A. whether the server is discovered immediately or after the acknowledgement of the administrator B. defines the scrub policy to be used upon discovery C. defines the management IP address to be associated to the server upon discovery D. reverts a -Series server from Cisco UCS domain mode to standalone mode E. defines the Cisco Host Upgrade Utility ISO file for the rack servers connected to the fabric interconnects Answer: AB Explanation:

[http://www.cisco.com/c/en/us/td/docs/unified\\_computing/ucs/sw/gui/config/guide/2-0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0/b\\_UCSM\\_GUI\\_Configuration\\_Guide\\_2\\_0\\_chapter\\_01100.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/2-0/b_UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_01100.html)

More free Lead2pass 300-175 exam new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDVDYyRldqb1AzenM> These Cisco 300-175 exam questions are all a small

selection of questions. If you want to practice more questions for actual 300-175 exam, use the links at the end of this document. Also you can find links for 300-175 VCE software that is great for preparation and self-assessment for Cisco 300-175 exam. 2017 Cisco 300-175 (All 255 Q&As) exam dumps (PDF&VCE) from Lead2pass: <https://www.lead2pass.com/300-175.html> [100% Exam Pass Guaranteed]